

**DAB Submersible borehole
pump stainless steel 304 2"
female thread 15A 230VAC
with 30m cable and control box
booster type S4 KIT 8/15 oil
cooling (7030921)**



TECHNICAL SPECIFICATIONS

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 technopolymer

Connection female thread

Type oil cooling

Voltage 230VAC

Max. temperature 40 °C

Outer ø 99 mm

Minimum medium temperature 0 °C
(continuous)

Maximum ambient temperature -10 °C

Minimum ambient temperature 40 °C

IP value IP68, class F

Type S4 KIT 8/15

Output Power 3 HP

Model with 30m cable and control box booster

Max. head 90 m

Size	2"
Weight	21.7 kg
Power	2.2 kW
Impellers	15
Ampere	15 A
Max flow rate	10.8 m ³ /h
Press	2 "
BEP Capacity	7.2
BEP Head	74.5
PORlh	89.4
PORhh	52.2
PORlq	8.6
PORhq	5
Efficiency	65,2 %
Packaging dimensions L/W/H	120 x 120 x 1519 mm


DIMENSIONS

Db	99 mm
H-1	1419 mm

ØDi-1

2"

ØDi-1



PRODUCT INFORMATION

Submersible borehole pump kit with pump body and motor, power supply cable, cord and control box.

Pump maximum diameter: 99 mm

Maximum amount of sand: 150 g/m³

Installation: Fixed in vertical position or horizontal installation with a cooling sleeve.

Motor: 4OL oil-filled two-pole asynchronous DAB motor

Last modified date: 26/05/2026

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>