

**DAB Submersible pump
stainless steel 304 2" female
thread 6,63A 230VAC stainless
steel type Feka VS 1000 M-A
with float switch (7030951)**



TECHNICAL SPECIFICATIONS

Colour stainless steel

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 stainless steel 304

Connection female thread

Max. temperature 50 °C

Minimum medium temperature 0 °C
(continuous)

Press 2 "

Maximum ambient temperature 40 °C

Minimum ambient temperature 0 °C

Type Feka VS 1000 M-A

Output Power 1,36 HP

Size 2"

Float included

Voltage 230VAC

Power 1 kW

MWC 11,8

Ampere 6,63 A

Max flow rate 24 m³/h

BEP Capacity 18.7

BEP Head 6.72

PORlh 8.63

PORhh 5

PORlq 13.09

PORhq 22.44

DIMENSIONS

Cb-1 98 mm



Db 170 mm

H 172 mm

L 492 mm

W-1 203 mm

ØDi-1 2 "



PRODUCT INFORMATION

Power cable: 10 metre H07RN-F, with plug for the single-phase version.

Installation: fixed or portable, vertical position.

Maximum immersion depth: 7 metre

Suitable for residential waste water as sewage containing solid matter with size up to 50 mm.

Last modified date: 10/03/2026

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>