Rain Bird Pop-up sprinkler plastic 3/4" female thread 40°-360° black type 5004-PC & FC (7008128)




RAIN



TECHNICAL SPECIFICATIONS

| Material plastic Capacity 3 - 36,6 l/min Connection female thread Angle 13/25 ° Max diameter 30.4 m Radius 7,6 - 15,2 m Radius 4bar 10,6 - 15,2 m Rec. press. 1.7 - 4.5 bar Type 5004-PC & FC Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° Riser height 10 cm | Colour | black |
|---|-------------------|-----------------------------|
| Connection female thread Angle 13/25 ° Max diameter 30.4 m Radius 7,6 - 15,2 m Radius 4bar 10,6 - 15,2 m Rec. press. 1.7 - 4.5 bar Type 5004-PC & FC Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Material | plastic |
| Angle 13/25 ° Max diameter 30.4 m Radius 7,6 - 15,2 m Radius 4bar 10,6 - 15,2 m Rec. press. 1.7 - 4.5 bar Type 5004-PC & FC Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Capacity | 3 - 36,6 l/min |
| Max diameter 30.4 m Radius 7,6 - 15,2 m Radius 4bar 10,6 - 15,2 m Rec. press. 1.7 - 4.5 bar Type 5004-PC & FC Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Connection | female thread |
| Radius 7,6 - 15,2 m Radius 4bar 10,6 - 15,2 m Rec. press. 1.7 - 4.5 bar Type 5004-PC & FC Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Angle | 13/25 ° |
| Radius 4bar 10,6 - 15,2 m Rec. press. 1.7 - 4.5 bar Type 5004-PC & FC Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Max diameter | 30.4 m |
| Rec. press. 1.7 - 4.5 bar Type 5004-PC & FC Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Radius | 7,6 - 15,2 m |
| Type 5004-PC & FC Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Radius 4bar | 10,6 - 15,2 m |
| Capacity 2.5bar 0,31-1,63 m³/h Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Rec. press. | 1.7 - 4.5 bar |
| Capacity 2bar 0,28-1,45 m³/h Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Туре | 5004-PC & FC |
| Capacity 3bar 0,34-1,79 m³/h Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Capacity 2.5bar | 0,31-1,63 m ³ /h |
| Capacity 4bar 0,40-2,06 m³/h Size 3/4" Sector adj. range 40°-360° | Capacity 2bar | 0,28-1,45 m ³ /h |
| Size 3/4" Sector adj. range 40°-360° | Capacity 3bar | 0,34-1,79 m ³ /h |
| Sector adj. range 40°-360° | Capacity 4bar | 0,40-2,06 m ³ /h |
| | Size | 3/4" |
| Riser height 10 cm | Sector adj. range | 40°-360° |
| | Riser height | 10 cm |





PRODUCT INFORMATION

The 5000 series is an ideal pop-up rotor for large gardens and professional applications that demand high versatility and durability.

The 5000 series suits perfect with the 5000 Rain Courtain nozzles and 5000 MPR nozzles. The 5000 series comes with many optional features such as the Plus (PL) Flow shutoff to reduce downtime on jobs by flushing rotors on the spot, PRS (R) pressure regulator to save water, SAM Seal-A-Matic check valve, Stainless Steel (SS) riser to prevent vandalism on public areas and a Purple cover (NP) for non-potable systems.

Pre-assembled with 3.0mm nozzle

Last modified date: 05/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

