Grundfos Multi-stage centrifugal pump stainless steel 1 1/4" 1A 400VAC type CRI 1S-13 A CA I V HQQV (7039618)



GRUNDFOS

bosta
bringing water to life


TECHNICAL SPECIFICATIONS


Material	stainless steel
Shaft	stainless steel 316
Pump body	stainless steel 316
Material impeller 1	stainless steel 304
Voltage	400VAC
Temperature range	-20°C - 90°C
Maximum ambient temperature	40 °C
Minimum ambient temperature	0 °C
Type	CRI 1S-13 A CA I V HQQV
Output Power	0.5 HP
Max. head	75 m
Size	1 1/4"
Power	0.37 kW
Impellers	13
Ampere	1 A
Max flow rate	1.1 m^3/h
Suction	1 1/4 "

Efficiency	73,8 %
Motor RPM	2770

DIMENSIONS

Cb-1	50 mm
Cb-2	50 mm
H-1	628 mm
L	162 mm
W-1	210 mm
ØDi-1	35 mm
ØDi-1	1 1/4 "
ØDi-2	35 mm
ØDi-2	1 1/4 "





PRODUCT INFORMATION

Grundfos CRI pumps are vertical, non-self-priming, multistage, in-line, centrifugal pumps for installation in pipe systems and mounting on a foundation, suitable for industrial applications. This design provides a more compact pump design and pipework. CR pumps are designed for a variety of applications ranging from the pumping of potable water to the pumping of chemicals. The pumps are therefore suitable for a wide range of pumping systems where the performance and material of the pump meet specific demands.

Last modified date: 27/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com