

**Amiad Automatic filter  
fibreglass reinforced nylon  
DN80 flange 8bar 100micron  
0,1 mm stainless steel 316 9-  
12VDC latch black/green 1 x 3"  
filter type Mini Sigma On-line  
(7038400)**



 **amiad**<sup>®</sup>  
WATER SYSTEMS

 **bosta**  
bringing water to life

# TECHNICAL SPECIFICATIONS

Colour	black/green
Type	Mini Sigma On-line
Material	fibreglass reinforced nylon
Material filter element	stainless steel 316
Material seal	EPDM
Connection	flange
Voltage	9-12VDC latch
Width	421 mm
Height	370 mm
Minimum inlet pressure	1.5 bar
Pressure	8 bar
Max. temp.	60 °C
Backflush Outlet	1 1/2 "
Capacity	50 m <sup>3</sup> /h
Model	1 x 3" filter
Filtration	100 micron
Size	DN80

Backflush flow rate 9,6 m<sup>3</sup>/h

Length 1258 mm

Weight 20 kg

Filter area 0.16 m<sup>2</sup>

Filtration 0,1 mm

## DIMENSIONS

Cr-1 225 mm

## PRODUCT INFORMATION

The Amiad Mini Sigma for online installations.

The Amiad ADI-P 12VDC controller with a 2W-Latch solenoid allows the user to monitor and control the filter from the Amiad app on your mobile via Bluetooth.

The app will provide the following information:

- DP and flush cycle counters.
- Alerts (low/high pressures) and low battery.
- Reports and performance history data.

Self-cleaning cycle is triggered by an integrated DP switch which is initiated by: a Pre-set 0.5 signal from DP switch, a time interval or a manual start.

Flushing time of 10 seconds.

Delivered with 1.5" flush valve.

**Last modified date: 10/03/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road

Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>