

**Hunter Pop-up sprinkler plastic
1 1/2" female thread 40° - 360°
30cm black type ST-1200-BR
(7032797)**



Hunter®

TECHNICAL SPECIFICATIONS

Colour	black
Type	ST-1200-BR
Material	plastic
Capacity	16,9 - 20,9 m ³ /h
Capacity	282 - 348 l/min
Connection	female thread
Length	30 cm
Sector adj. range	40° - 360°
Angle	22,5°
Max diameter	70.2 m
Riser height	8 cm
Radius	31,4 - 36,6 m
Rec. press.	6,9 - 8,3 bar
Size	1 1/2"

PRODUCT INFORMATION

The cost-effective ST-1200-BR is the ideal riser-mounted solution for pastures, corrals, arenas, dust control, and wash-down watering.

- Nozzle choices: 5 (included)
- Standard nozzle: #12
- Nozzle range: #10 to #18
- Nozzle trajectory: 22.5°
- Isolated, grease-lubricated gear drive
- Nozzle barrels: short and long (included)
- Movable stops (left and right) arc adjustment
- Arc setting: 40° to non-reversing 360°
- Ratcheting nozzle turret
- Radius: 20.4 m to 35.1 m
- Flow: 6.13 to 29.76 m³/hr; 102.1 to 495.9 l/min
- Recommended pressure range: 2.0 to 6.0 bar; 200 to 600 kPa

Last modified date: 27/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>