

**NaanDan Drip irrigation hose**  
**PE 16 mm x 0,9 mm 1,0ltr/h**  
**50cm black 500m type Topdrip**  
**PC AS (7040233)**



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

|                  |               |
|------------------|---------------|
| Colour           | black         |
| Type             | Topdrip PC AS |
| Material         | PE            |
| Opening pressure | 1.0 bar       |
| Rec. press.      | 0.5 - 3.5 bar |
| Flow             | 1,0 ltr/h     |
| Size             | 16 mm         |
| Length           | 500 m         |
| Inner ø          | 14,2 mm       |
| Dripper spacing  | 50 cm         |
| Wall thickness   | 35 mil        |
| Wall thickness   | 0,9 mm        |

## PRODUCT INFORMATION

The Naan PC (Pressure Compensated) round dripper with 2 outlet holes gives the dripline additional strength against recoiling and resistance against clogging.

Pressure Regulating Range: 0.5 - 4.0 bar.

Recommended filtration: 130 micron.

Maximum Lateral Length at 0% slope.

**Last modified date: 07/10/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>