Hunter Pop-up sprinkler plastic 2" female thread 40° - 360° black type ST-1700-V-B Valve in head (7032798)



Hunter®



TECHNICAL SPECIFICATIONS

Colour	black
Туре	ST-1700-V-B
Material	plastic
Capacity	16,9 - 20,9 m ³ /h
Capacity	282 - 348 l/min
Connection	female thread
Sector adj. range	40° - 360°
Angle	22,5 °
Riser height	8 cm
Radius	31,4 - 36,6 m
Rec. press.	6,9 - 8,3 bar
Size	2"
Туре	Valve in head
Max diameter	96 m

PRODUCT INFORMATION



The ST-1700-V-B is a gear-driven synthetic turf rotor designed for cooling, cleaning, and flushing large synthetic sports fields. The rotor features an integrated valve-in-head and actuator design for total-top-serviceability.

- Nozzle choices: 5
- Standard nozzle: 20 pre mounted
- Nozzle range: 16, 18, 22, 24 and 26 included
- Nozzle trajectory: 25°
- Total-Top-Service (TTS) design provides convenient no-dig servicing
- Valve-in-head configuration simplifies installation
- Isolated, grease-lubricated gear drive
- Factory-installed rubber logo cap
- Arc adjustment: movable stops for left/right arc adjustment
- Ratcheting nozzle turret
- Radius: 32 to 48 m
- Flow: 21.0 to 58.8 m3/hr; 350 to 980 l/min
- Operating pressure range: 4.0 to 8.0 bar; 400 to 800 kPa
- Arc setting: 40° to non-reversing 360°
- Speed of rotation: 80 seconds at 6.0 bar; 600 kPa (single 180° sweep)
- Precipitation rate: 45 mm/hr approximately
- Warranty period: 5 years component parts

Last modified date: 07/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

