NaanDan Drip irrigation hose PE 16 mm x 1,0 mm 39mil 4bar 130micron 1,1ltr/h 20cm black 500m type Amnon PC CNL (7020652)



NaanDan by Rivulis



TECHNICAL SPECIFICATIONS

Colour	black
Туре	Amnon PC CNL
Material	PE
Filtration	130 micron
Filtration	120 mesh
Opening pressure	1 bar
Pressure	4 bar
Rec. press.	1 - 4 bar
Flow	1,1 ltr/h
Size	16 mm
Length	500 m
Inner ø	14 mm
Max. Length	120 m
Dripper spacing	20 cm
Wall thickness	39 mil
Wall thickness	1,0 mm



PRODUCT INFORMATION

The Amnon CNL (Compensated Non-Leakage) flat dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 1.0 bar. Closing Pressure: 0.2 bar.

Pressure Regulating Range: 1.0 - 4.0 bar. Recommended filtration: 130 micron. Maximum Lateral Length at 0% slope.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in bags with soilless media such as strawberries.

Last modified date: 05/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

