

# Profec Rainwater supply manager 5bar black DVGW type Mono rain basic S with self priming pump and pressure switch (7036642)



# TECHNICAL SPECIFICATIONS

|        |       |
|--------|-------|
| Colour | black |
|--------|-------|

|                  |       |
|------------------|-------|
| Max. temperature | 50 °C |
|------------------|-------|

|     |      |
|-----|------|
| MWC | 42,5 |
|-----|------|

|      |                   |
|------|-------------------|
| Type | Mono rain basic S |
|------|-------------------|

|      |  |
|------|--|
| Type | with self priming pump and pressure switch |
|------|--|

|               |                       |
|---------------|-----------------------|
| Max flow rate | 6.6 m <sup>3</sup> /h |
|---------------|-----------------------|

|          |       |
|----------|-------|
| Pressure | 5 bar |
|----------|-------|

## PRODUCT INFORMATION

Complete and easy-to-connect solution for the needs-based make-up of drinking water in the consumer network when the rainwater tank is not full. This unit is compliant with DIN 1988 / EN 1717 standards and has a make-up quantity of 60 l/min (at 4.5 bar), including a 20m sensor. It also includes pressure increase capabilities for optimal performance.

**Last modified date: 11/03/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>