

**NaanDan Dripper set plastic 4  
mm x 4/7 mm push-in x barbed  
1,3ltr/h 80cm white type Click  
Tif, PC CNL (7020670)**



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

|                  |                   |
|------------------|-------------------|
| Colour           | white             |
| Type             | Click Tif, PC CNL |
| Material         | plastic           |
| Connection       | push-in x barbed  |
| Opening pressure | 0,8 - 0,3 bar     |
| Rec. press.      | 1 - 4 bar         |
| Flow             | 1,3 ltr/h         |
| Size             | 4 mm x 4/7 mm     |
| Length           | 80 cm             |

## PRODUCT INFORMATION

The ClickTif CNL (Compensated Non-Leakage) on-line button dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 0.8 bar.

Closing Pressure: 0.3 bar.

Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar.

Minimum pressure at lateral end: 0.8 bar; Lateral Length exceeding 800m is not recommended.

For fitting into PE40 pipe, punch 3mm hole.

Recommended filtration: 130 micron.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in tunnels or greenhouses such as strawberries, peppers, tomato, cucumber, raspberries, eggplants, etc.

**Last modified date: 09/03/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>