

**Hunter Pop-up sprinkler plastic
1" female thread 50°-360°
black type I-25-04-SS-HS
(7026276)**



Hunter®

TECHNICAL SPECIFICATIONS

Colour	black
Material	plastic
Capacity	0,82 - 7,24 m ³ /h
Capacity	13,6 - 120,2 l/min
Connection	female thread
Sector adj. range	50°-360°
Angle	25 °
Max diameter	43.2 m
Radius	11,9 - 21,6 m
Rec. press.	2,5 - 7 bar
Type	I-25-04-SS-HS
Size	1"
Riser height	10 cm

Type I-40														
Nr. 41			Nr. 42			Nr. 43			Nr. 44			Nr. 45		
Bar	Q	R	Bar	Q	R	Bar	Q	R	Bar	Q	R	Bar	Q	R
3.5	2.32	13.4	3.5	2.50	14.0	3.5	3.23	15.5	4.0	4.54	17.7	4.0	5.00	18.3
4.0	2.61	13.4	4.0	2.80	14.3	4.0	3.52	15.8	5.0	4.95	17.7	5.0	5.52	18.9
5.0	2.86	13.7	5.0	3.07	14.9	5.0	3.70	15.8	5.5	5.41	18.3	5.5	5.88	19.5
5.5	3.07	14.0	5.5	3.27	15.2	5.5	4.11	16.2	6.0	5.66	18.3	6.0	6.25	19.8



PRODUCT INFORMATION

The Hunter I-25 Strong as iron. That's the I-25 sprinkler. As it has an irrigation radius of 12 to 21 metres, this rotor can be used in zones of different sizes. Playing fields, lawns, flowerbeds: no project is too much. Its compact design can be supplied with an optional stainless steel riser. The I-25 is a reliable, strong and sustainable choice. Let the Hunter I-25 do the hard work for you, day in, day out. Now there's no need for you to do it.

Last modified date: 24/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>