

Tavlit Automatic filter station fibreglass reinforced nylon 2" 10bar 105micron disc 9-12VDC latch black type TVDSA Stand Alone (7031300)



TECHNICAL SPECIFICATIONS

Colour	black
Type	TVDSA
Material	fibreglass reinforced nylon
Material filter element	disc
Material seal	EPDM
Backflush flow rate	6,5 m ³ /h
Type	Stand Alone
Length	1050 mm
Voltage	9-12VDC latch
Width	310 mm
Height	1080 mm
Minimum inlet pressure	1.5 bar
Pressure	10 bar
Capacity	20 m ³ /h
Filtration	105 micron
Size	2"
Filter area	1100 m ²

PRODUCT INFORMATION

TVD patented automatic disc filtration saves water and energy by using air as well as water in the flushing process.

The venturi devices that are inserted at the spine's inlets introduce air during the flushing process to enhance it.

The mixture of air and water enables a more efficient and shorter flushing, therefore saving water, enabling flushing at a low pressure of 1.5 bar and a shortening of the flushing time.

The use of air also cushions the discs, thereby reducing friction and prolonging the life of the disc element.

When the head loss reaches a preset value of 0.5b-0.7b, the controller will start flushing one filter after the other.

Flushing cycle will take from 12 to 30 seconds, depending on the dirt load.

During flushing the flow to the field is uninterrupted.

Minimum flushing pressure required: 1.5bar.

Flushing flow rate at 1.5bar: 6.5m³/h.

Last modified date: 10/03/2026

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>