

# Norsup UV & Ozone disinfection unit 63 mm x 2" glue socket x female thread 2.5bar type AOP 75 (7043036)



 **NORSUP** 3 YEARS WARRANTY

# TECHNICAL SPECIFICATIONS

Type	AOP 75
Connection	glue socket x female thread
Pressure	2.5 bar
Capacity Qmax	23 m <sup>3</sup> /h
Size	63 mm x 2"
Power	75 W
Max. pool vol.	100 m <sup>3</sup>

## PRODUCT INFORMATION

The Norsup AOP, Advanced Oxidation Process, combines the benefits of ozone and UV-C into one device. It effectively oxidises the micro-pollutants in the water and thereby reduces any organic and inorganic pollution. The unit disinfects the water effectively, as well as de-activating any chlorine resistant organisms. The Norsup AOP is designed in a way that ensures all ozone in the water is used during the AOP process, therefore no de-ozoneation device is needed.

Features:

- Triple disinfection: ozone, OH radicals and UV-C
- 9000 hours lifetime of the lamp for ozone and UV-C production
- A stand-alone electronic ballast to guarantee an efficient and stable power supply
- Up to 35% more UV-C yield thanks to reflection by its stainless steel reactor
- Duplex stainless-steel housing, suitable for use in chlorine and salt electrolysis pools

**Last modified date: 27/05/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>