

**Profec Water meter cast iron
DN50 DIN flange 10bar 15m³/h
blue LXXG type paddle
horizontal (7021129)**



TECHNICAL SPECIFICATIONS

Colour	blue
Type	paddle
Material	cast iron
Model	LXXG
Material flange	cast iron
Material seal	rubber reinforced with nylon
Connection	DIN flange
Type	horizontal
Min. temp.	0.1 °C
Pressure	10 bar
Max. temp.	40 °C
Capacity	25 m ³ /h
Capacity Qmax	30 m ³ /h
Capacity Qn	15 m ³ /h
Size	DN50
Q1 ISO 4064 (2005)	1 m ³ /h
Q3 ISO 4064 (2005)	25 m ³ /h

Q4 ISO 4064 (2005)	31.25 m ³ /h
--------------------	-------------------------

Min. reading	0.0002 m ³ /h
--------------	--------------------------

Max. reading	999.999 m ³ /h
--------------	---------------------------

Length	200 mm
--------	--------

Diam.	2 "
-------	-----

PCD	125 mm
-----	--------

DIMENSIONS

H	248 mm
---	--------

Install. length	200
-----------------	-----

PCD	125 mm
-----	--------

PRODUCT INFORMATION

Specifically for natural source irrigation installations.

The paddle wheel impeller helps to avoid damage to the meter by stones or other materials which might be sucked in.

Dry display.

Last modified date: 24/05/2026

Bosta UK Ltd.
Reflection House
Olding Road

Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>