# NaanDan Drip irrigation hose PE 16 mm x 1,0 mm 39mil 4bar 130micron 0,5ltr/h 20cm black 500m type Amnon PC CNL (7024185)



NaanDan
by Rivulis

bosta
bringing water to life

# TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Colour | black |
| Type | Amnon PC CNL |
| Material | PE |
| Filtration | 130 micron |
| Filtration | 120 mesh |
| Flow | 0,5 ltr/h |
| Opening pressure | 1 bar |
| Pressure | 4 bar |
| Rec. press. | 1 - 4 bar |
| Size | 16 mm |
| WebshopURL | https://www.bosta.com/en-gb/naandan-drip-irrigation-hose-pe-16-mm-x-1-0-mm-39mil-4bar-130micron-0-5ltr-h-20cm-black-500m-type-amnon-pc-cnl-7024185 |
| Length | 500 m |
| Inner ø | 14 mm |
| Max. Length | 180 m |
| Dripper spacing | 20 cm |
| Wall thickness | 39 mil |

| | |
|---|---|
| Wall thickness | 1,0 mm |

# PRODUCT INFORMATION

The Amnon CNL (Compensated Non-Leakage) flat dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.
Opening Pressure: 1.0 bar.
Closing Pressure: 0.2 bar.
Pressure Regulating Range: 1.0 - 4.0 bar.
Recommended filtration: 130 micron.
Maximum Lateral Length at 0% slope.
Coefficient of manufacturing Variation (CV): 3%.
Application: ideal for pulse irrigation in crops growing in bags with soilless media such as strawberries.

## Last modified date: 01/11/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com