

# DAB Assembled pump sump PE 5,13A 230VAC black type PE612 Complete (7038492)



**DAB**<sup>®</sup>  
MAKING WATER EASY

# TECHNICAL SPECIFICATIONS

Colour	black
Type	PE612 Complete
Material	PE
Pump body	stainless steel 304
Max. head	9.6 m
Voltage	230VAC
Max. temperature	50 °C
Minimum medium temperature (continuous)	0 °C
Max flow rate	24 m <sup>3</sup> /h
Maximum ambient temperature	40 °C
Output Power	1 HP
Power	0.75 kW
Ampere	5,13 A

## PRODUCT INFORMATION

PE pump sump fitted with Feka VS 750 MA stainless steel submersible sewage pump. Ideally suited for wastewater and sewage water with solids not exceeding 50mm. Fully assembled and

equipped with DSD guide system - PE pump pit  $\varnothing$  600 x 1200 mm - Flat bottom - 1x inlet socket  $\varnothing$  125 mm - 1x outlet  $\varnothing$  63 mm - 1x cable duct  $\varnothing$  75 mm - 1x Feka VS 750 MA 230 Volt 50 Hz - 1x installation set consisting of DSD guide system with beam damper - 1x cable protection pipe 75 mm, 5 mtr - 1x cast iron manhole cover Class D (heavy duty) - 1x concrete ledge 900\*900\*200 mm - 1x AS1 flood valve with float switch Application: For pumping rainwater and/or sewage containing max 50mm solids

**Last modified date: 27/05/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>