

# Profec Rainwater supply manager 4bar black DVGW type Mono rain smart with self priming pump including smart control (7036637)



# TECHNICAL SPECIFICATIONS

Colour	black
Max. head	42,5 m
Type	with self priming pump including smart control
Max. temperature	50 °C
Max flow rate	6.6 m <sup>3</sup> /h
Type	Mono rain smart
Pressure	4 bar

## PRODUCT INFORMATION

The Profec rainwater supply manager mono with self-priming pump is a complete and compact house station designed for the fully automatic supply of rainwater from a rainwater storage tank. It is also equipped for the needs-based drinking water refill (EN 1717 / DIN 1988 / DVGW W540) in the consumer network when the rainwater supply is exhausted. This rainwater supply manager can save up to 40% of electricity and has an adjustable control pressure, flushing program, leak warning system, temperature monitoring, and is updatable with remote monitoring. You can connect it to your PC or mobile phone, and it includes automatic backwater detection, automatic monitoring function, dry-running detection with auto-start, level indicator, pump control, Standby 2 W, H max. 45 m, and Q max. 110 l/min.

**Last modified date: 27/05/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road

Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>