

**NaanDan Drip irrigation hose**  
**PE 20 mm x 1,2 mm 47mil 4bar**  
**130micron 1,6ltr/h 50cm black**  
**300m type Amnon PC AS**  
**(7018986)**



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

|                  |             |
|------------------|-------------|
| Colour           | black       |
| Type             | Amnon PC AS |
| Material         | PE          |
| Filtration       | 130 micron  |
| Filtration       | 120 mesh    |
| Flow             | 1,6 ltr/h   |
| Opening pressure | 0,5 bar     |
| Pressure         | 4 bar       |
| Rec. press.      | 0,5 - 4 bar |
| Size             | 20 mm       |
| Length           | 300 m       |
| Inner ø          | 17,6 mm     |
| Max. Length      | 340 m       |
| Dripper spacing  | 50 cm       |
| Wall thickness   | 47 mil      |
| Wall thickness   | 1,2 mm      |

# PRODUCT INFORMATION

The Amnon PC (Pressure Compensated) AS (Anti-Siphon) flat dripper reduces suction at the draining stage to prevent it from blocking.

Opening Pressure: 0.5 bar.

Pressure Regulating Range: 0.5 - 4.0 bar.

Recommended filtration: 130 micron.

Maximum Lateral Length at 0% slope.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for Subsurface Drip Irrigation (SDI) as well as for above the ground irrigation.

**Last modified date: 05/10/2025**

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>