NaanDan Drip irrigation hose PE 20 mm x 1,2 mm 47mil 4bar 130micron 1,1ltr/h 20cm black 300m type Amnon PC AS (7020636)

NaanDan
by Rivulis

bosta
bringing water to life

TECHNICAL SPECIFICATIONS

Colour	black
Type	Amnon PC AS
Material	PE
Filtration	130 micron
Filtration	120 mesh
Flow	1,1 ltr/h
Opening pressure	0,5 bar
Pressure	4 bar
Rec. press.	0,5 - 4 bar
Size	20 mm
Length	300 m
Inner ø	17,6 mm
Max. Length	200 m
Dripper spacing	20 cm
Wall thickness	47 mil
Wall thickness	1,2 mm

PRODUCT INFORMATION

The Amnon PC (Pressure Compensated) AS (Anti-Siphon) flat dripper reduces suction at the draining stage to prevent it from blocking.
Opening Pressure: 0.5 bar.
Pressure Regulating Range: 0.5 - 4.0 bar.
Recommended filtration: 130 micron.
Maximum Lateral Length at 0% slope.
Coefficient of manufacturing Variation (CV): 3%.
Application: ideal for Subsurface Drip Irrigation (SDI) as well as for above the ground irrigation.

Last modified date: 05/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com