

Waterco Commercial sand filter fibreglass 3"/90mm flange 2,5bar grey type SMD1050 (7029500)




WATERCO
EUROPE LTD
Water, the liquid of life

TECHNICAL SPECIFICATIONS

Colour	grey
Material	fibreglass
Connection	flange
Pressure	2,5 bar
Max. temp.	50 °C
Type	SMD1050
Capacity	26 m ³ /h
Size	3"/90mm
Sand	1410 kg
Filter area	0.87 m ²
Max flow rate	35 m ³ /h
Max. pool vol.	130 m ³

DIMENSIONS

A	918 mm
B	1110 mm
C	1930 mm



PART NO.	SIZE	A mm	B mm	C mm	W mm	H mm	P mm	E mm	F mm	K mm
702490	2'x3' mm	617	772	1089	334	362	391	1220	1328	15
702495	3'x6' mm	824	1033	1878	570	583	548	1406	1518	180
702500	3'x6' mm	751	1113	1800	570	583	548	1190	1210	200
702501	3'x6' mm	877	1239	1835	570	583	548	1154	1264	180
702502	3'x6' mm	1080	1442	1889	570	583	548	1204	1274	230
702503	3'x6' mm	1184	1544	1904	570	583	548	1157	1267	200
702504	4'x10' mm	1195	1644	1884	843	274	839	1397	418	180
702505	4'x10' mm	1825	1809	1885	843	474	624	121	415	225
702506	4'x10' mm	1954	2042	2093	843	474	629	106	420	200

PART NO.	SIZE	V mm	H mm	L mm	X mm	Y mm	Z mm	J mm	S mm	T mm
702490	2'x3' mm	1425	1383	120	1850	1480	1593	878	1229	1033
702495	3'x6' mm	1080	1442	1387	1839	1180	1180	780	1406	1030
702500	3'x6' mm	1005	1470	176	1845	1482	1775	1045	1100	744
702501	3'x6' mm	1050	1400	176	1850	1536	1180	1045	1164	768
702502	3'x6' mm	1815	1880	218	1870	1586	1830	1202	1204	848
702503	3'x6' mm	1815	1800	218	1820	1539	1839	1202	1197	796
702504	4'x10' mm	1815	1430	218	1909	787	1839	1202	1180	787
702505	4'x10' mm	1710	1470	315	1860	787	1830	1185	1183	787
702506	4'x10' mm	1765	1850	245	1915	787	1829	1185	1180	799

PRODUCT INFORMATION

Waterco commercial sand filter SMD is a micron fibreglass filter which embody the latest in fibreglass winding technology. The digitally controlled filament winding machine faultlessly winds continuous strands of high quality fibreglass filament under controlled tension to create a seamless one-piece vessel with refined consistency and superior quality. There are no welds or seams or special tank linings which can corrode or electrolyse. Its "Fish Tail" lateral configuration eliminates any "dead legs" by improving water flow distribution through the filter bed. SMD model is available in 2.5 bar, 4 bar, 6 bar, 8 bar and 10 bar pressure ratings.

Features:

- 1m bed depth
- Ultra smooth bobbin finish
- Large double yoke lid with lifting eye
- Large clear sight glass
- Large stable base
- Quick connect unions
- Fish Tail lateral
- Optional nozzle plate
- 10 years tank warranty

Last modified date: 10/03/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>