

VGE Pro Low pressure lamp UV system stainless steel DN225 flange 6bar type Basic 975-306 (7030120)



VGE PRO
UV DISINFECTION SOLUTIONS

TECHNICAL SPECIFICATIONS

Material	stainless steel
----------	-----------------

Pressure	6 bar
----------	-------

Type	Basic 975-306
------	---------------

Capacity Qmax	391.2 m ³ /h
---------------	-------------------------

Size	DN225
------	-------

Connection	flange
------------	--------

Power	975 W
-------	-------

PRODUCT INFORMATION

VGE Pro Inox system provides perfect disinfection thanks to its high power and advanced treatment around the UV lamp. It uses a high quality 316L stainless steel reactor, and the high quality welding process passes all the leak tests. The pickling and passivation treatment improves the corrosion resistance and lifetime of the unit dramatically. The glass pearl coating gives the unit a premium outlook. VGE Pro Inox system is equipped with the unique Smart Pin technology, which makes it possible to replace the lamp safely even though the system is filled with water and pressure. It is equipped with a basic controller, which is fitted with an electronic ballast to drive the lamp(s).

Features:

- High corrosion resistance
- Leak tested
- Smart Pin technology
- UV radiation reflection
- Easy to install
- Basic controller

Last modified date: 26/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>