Profec Butterfly valve ductile iron (GGG40) epoxy coating DN100 flange 10bar DN100 blue PN6/10/16 type 600 (0401853)



PROFEC

bosta
bringing water to life


TECHNICAL SPECIFICATIONS

Colour	blue
Type	600
Material	ductile iron (GGG40)
Surface treatment	epoxy coating
Operation	lever
Colour lever	black
Handle material	malleable cast iron
Material valve	ductile iron
Material spindle	stainless steel 316
Seat material	EPDM
Material housing	ductile iron (GGG40)
Material seal	EPDM
Connection	flange
Flange	PN6/10/16
Temperature range	0°C - 90°C
Pressure	10 bar
Size	DN100

WebshopURL	https://www.bosta.com/en-gb/profec-butterfly-valve-ductile-iron-ggg40-epoxy-coating-dn100-flange-10bar-dn100-blue-pn6-10-16-type-600-0401853
DN	100
Width	52 mm
Height	351 mm
Torque	30 Nm
Bolt hole	18 mm
Holes	8

DIMENSIONS

Construction length	din 3202 k1, iso 5752
Ct-1	228 mm
PCD	170/180 mm
R	260 mm
W-1	52 mm
W-2	104 mm



Last modified date: 01/11/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

bosta
bringing water to life