

**DAB Submersible pump  
reinforced plastic 1 1/4" male  
thread 1,5A 230VAC green  
type Nova UP 300 M-AE  
(7030947)**



# TECHNICAL SPECIFICATIONS

Colour	green
Material	reinforced plastic
Pump body	technopolymer
Material impeller 1	technopolymer
Connection	male thread
Float	integrated
Voltage	230VAC
Max. temperature	35 °C
Minimum medium temperature (continuous)	0 °C
Press	1 1/4 "
Maximum ambient temperature	40 °C
Minimum ambient temperature	0 °C
Type	Nova UP 300 M-AE
Output Power	0,28 HP
Size	1 1/4"
Power	0.21 kW

MWC 7,6

Ampere 1,5 A

Max flow rate 9 m<sup>3</sup>/h

BEP Capacity 10.8

BEP Head 5.74

PORlh 7.17

PORhh 4.47

PORlq 7.56

PORhq 12.96

## DIMENSIONS



Db 160 mm

H-1 75.9 mm

H-2 296.2 mm

W-1 206 mm

ØDi-1 1 "



# PRODUCT INFORMATION

Installation: vertical, fixed or portable. Max. immersion depth: 7 metres.

Pump can be used with liquids containing solid particles of up to 10 mm in size.

Suited for narrow well installation requiring automatic suction up to 2/3 mm. Filter is removable.

Dry operation of max. 1 minute.

**Last modified date: 14/03/2026**

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>