Amiad Automatic filter fibreglass reinforced nylon 2" male thread 8bar 130micron 0,13 mm stainless steel 316 9-12VDC latch black/green type Mini Sigma On-line (7028312)



amiad WATER SYSTEMS

bosta bringing water to life

TECHNICAL SPECIFICATIONS

Colour	black/green
Type	Mini Sigma On-line
Material	fibreglass reinforced nylon
Capacity	30 m^3/h
Material filter element	stainless steel 316
Material seal	EPDM
Size	2"
Connection	male thread
Length	1096 mm
Voltage	9-12VDC latch
Width	421 mm
Weight	16 kg
Height	370 mm
Minimum inlet pressure	1.5 bar
Pressure	8 bar
Backflush Outlet	1 1/2 "
Filtration	130 micron

Backflush flow rate	8,7 m^3/h
WebshopURL	https://www.bosta.com/en-gb/amiad-automatic-filter-fibreglass-reinforced-nylon-2-male-thread-8bar-130micron-0-13-mm-stainless-steel-316-9-12vdc-latch-black-green-type-mini-sigma-on-line-7028312
Filter area	0.12 m^2
Filtration	0,13 mm

DIMENSIONS

Cr-1	225 mm

PRODUCT INFORMATION

The Amiad Mini Sigma for online installations.
The Amiad ADI-P 12VDC controller with a 2W-Latch solenoid allows the user to monitor and control the filter from the Amiad app on your mobile via Bluetooth.
The app will provide the following information:
- DP and flush cycle counters.
- Alerts (low/high pressures) and low battery.
- Reports and performance history data.

Self-cleaning cycle is trigged by an integrated DP switch which is initiated by: a Pre-set 0.5 signal from DP switch, a time interval or a manual start.
Flushing time of 10 seconds.
Delivered with 1.5" flush valve.

Last modified date: 02/11/2026

Bosta UK Ltd.
Reflection House

Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

bosta
bringing water to life