

NaanDan Drip irrigation hose
PE 20 mm x 1,2 mm 47mil 4bar
130micron 1,6ltr/h 30cm black
300m type Amnon PC AS
(7018985)



NaanDan
by Rivulis

TECHNICAL SPECIFICATIONS

| | |
|------------------|-------------|
| Colour | black |
| Type | Amnon PC AS |
| Material | PE |
| Filtration | 130 micron |
| Filtration | 120 mesh |
| Flow | 1,6 ltr/h |
| Opening pressure | 0,5 bar |
| Pressure | 4 bar |
| Rec. press. | 0,5 - 4 bar |
| Size | 20 mm |
| Length | 300 m |
| Inner ø | 17,6 mm |
| Max. Length | 240 m |
| Dripper spacing | 30 cm |
| Wall thickness | 47 mil |
| Wall thickness | 1,2 mm |

PRODUCT INFORMATION

The Amnon PC (Pressure Compensated) AS (Anti-Siphon) flat dripper reduces suction at the draining stage to prevent it from blocking.

Opening Pressure: 0.5 bar.

Pressure Regulating Range: 0.5 - 4.0 bar.

Recommended filtration: 130 micron.

Maximum Lateral Length at 0% slope.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for Subsurface Drip Irrigation (SDI) as well as for above the ground irrigation.

Last modified date: 05/10/2025

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E enquiries@bosta.co.uk

<http://www.bosta.com>