

**Profec Water meter dry cast
iron DN100 DIN flange 10bar
0,01A 60m³/h 24V blue
LXLC/FX type Woltman
horizontal with pulse (7019376)**



TECHNICAL SPECIFICATIONS

Colour	blue
Type	Woltman
Material	cast iron
Model	LXLC/FX
Material flange	cast iron
Material seal	rubber reinforced with nylon
Connection	DIN flange
Pulse	100 ltr
Type	horizontal with pulse
Voltage	24V
Pressure	10 bar
Max. temp.	40 °C
Capacity	100 m ³ /h
Capacity Qmax	120 m ³ /h
Capacity Qn	60 m ³ /h
Size	DN100
Q1 ISO 4064 (2005)	1.25 m ³ /h

Q3 ISO 4064 (2005)	100 m ³ /h
Q4 ISO 4064 (2005)	125 m ³ /h
Min. reading	0.002 m ³ /h
Max. reading	999.999 m ³ /h
Length	250 mm
Diam.	4 "
PCD	180 mm

DIMENSIONS

H	289 mm
Install. length	250
PCD	180 mm

PRODUCT INFORMATION

Output signal: Parallel reed contact (3 wire)

Last modified date: 25/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds

Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>