

**Tavlit Semi-Automatic filter  
fibreglass reinforced nylon 2"  
male thread 10bar 120micron  
0,12 mm stainless steel 316  
black type Adir Super (7028551)**



# TECHNICAL SPECIFICATIONS

Colour	black
Type	Adir Super
Material	fibreglass reinforced nylon
Material filter element	stainless steel 316
Filtration	120 micron
Filtration	120 mesh
Material seal	EPDM
Connection	male thread
Backflush flow rate	5,4 m <sup>3</sup> /h
Length	280 mm
Weight	4.5 kg
Minimum inlet pressure	2 bar
Pressure	10 bar
Backflush Outlet	1 "
Capacity	25 m <sup>3</sup> /h
Size	2"
Filter area	0.095 m <sup>2</sup>

Filtration 0,12 mm

Height 720 mm

## PRODUCT INFORMATION

Standard 2 action cleaning system.

Comes with a standard pressure DP indicator that shows the user that the filter is dirty and needs flushing (preset value set to 0.5b).

Flushing is performed by opening the drain valve and rotating the handle.

During flushing, the flow to the field is uninterrupted.

Minimum flushing pressure required: 2bar.

Flushing flow rate: 2bar = 5.4m<sup>3</sup>/h, 3bar = 6.8m<sup>3</sup>/h.

We recommend to install a manual valve (open/close) in the upstream.

**Last modified date: 06/10/2025**

Bosta UK Ltd.

Reflection House

Olding Road

Bury St. Edmunds

Suffolk

IP33 3TA

T +44 (0) 1284 716580

E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)

<http://www.bosta.com>