# DAB Deep well pump stainless steel 304 1" female thread 6,1A 230VAC with 15m cable and control box booster type Micra 100M oil cooling (7030894)







# **TECHNICAL SPECIFICATIONS**

Material stainless steel 304 Pump body stainless steel 304 Material impeller 1 noryl GFN2 female thread Connection oil cooling Type Voltage 230VAC Max. temperature 35 °C Outer ø 74 mm Minimum medium temperature 0 °C (continuous)  $2.7 \, \text{m}^3/\text{h}$ Max flow rate 1 " Press **BEP Capacity** 1.8 IP value **IP68** Micra 100M Type **Output Power** 1 HP Model with 15m cable and control box booster




| Size      | 1"      |
|-----------|---------|
| Weight    | 13.6 kg |
| Power     | 0.75 kW |
| Impellers | 30      |
| MWC       | 90      |
| Ampere    | 6,1 A   |
| BEP Head  | 56      |
| PORIh     | 70.1    |
| PORhh     | 39.6    |
| PORIq     | 1.3     |
| PORhq     | 2.2     |

# **DIMENSIONS**

| ØDi-1 | 1 "     |
|-------|---------|
| H-1   | 1390 mm |
| Db    | 74 mm   |







## **PRODUCT INFORMATION**

Includes assembled 15m cable and control box booster.

Pumped liquid: clean, free of solids and abrasives, non-viscous, non-aggressive, and chemically neutral, with properties similar to water.

Maximum permitted amount of sand: 40 g/m3.

Installation: in 3" wells or larger, tanks and cisterns, vertical position. In case of horizontal installation, ensure a minimum load on the thrust assembly.

### Last modified date: 07/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

