

# DAB Submersible borehole pump stainless steel 304 1" female thread 6,1A 230VAC with 15m cable and control box booster type Micra 100M oil cooling (7030894)



# TECHNICAL SPECIFICATIONS

Material stainless steel 304

Pump body stainless steel 304

Material impeller 1 noryl GFN2

Connection female thread

Type oil cooling

Voltage 230VAC

Max. temperature 35 °C

Outer ø 74 mm

Minimum medium temperature 0 °C  
(continuous)

Max flow rate 2.7 m<sup>3</sup>/h

Press 1 "

BEP Capacity 1.8

IP value IP68

Type Micra 100M

Output Power 1 HP

Model with 15m cable and control box booster

Size 1"

Weight 13.6 kg

Power 0.75 kW

Impellers 30

MWC 90

Ampere 6,1 A

BEP Head 56

PORlh 70.1

PORhh 39.6

PORlq 1.3


PORhq 2.2

## DIMENSIONS

Db 74 mm

H-1 1390 mm

ØDi-1 1"



**bosta**  
bringing water to life

# PRODUCT INFORMATION

Includes assembled 15m cable and control box booster.

Pumped liquid: clean, free of solids and abrasives, non-viscous, non-aggressive, and chemically neutral, with properties similar to water.

Maximum permitted amount of sand: 40 g/m<sup>3</sup>.

Installation: in 3" wells or larger, tanks and cisterns, vertical position. In case of horizontal installation, ensure a minimum load on the thrust assembly.

**Last modified date: 14/03/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>