

**Profec Water meter cast iron  
DN125 DIN flange 16bar  
100m<sup>3</sup>/h blue LXLC(R) type  
Woltman horizontal (7021133)**



# TECHNICAL SPECIFICATIONS

Colour	blue
Type	Woltman
Material	cast iron
Model	LXLC(R)
Material flange	cast iron
Material seal	rubber reinforced with nylon
Connection	DIN flange
Type	horizontal
Max. reading	999.999 m <sup>3</sup> /h
Temperature range	0°C - 40°C
Pressure	16 bar
Capacity	160 m <sup>3</sup> /h
Capacity Qmax	200 m <sup>3</sup> /h
Capacity Qn	100 m <sup>3</sup> /h
Size	DN125
Q1 ISO 4064 (2005)	3.1 m <sup>3</sup> /h
Q3 ISO 4064 (2005)	160 m <sup>3</sup> /h

Q4 ISO 4064 (2005) 312.5 m<sup>3</sup>/h

Min. reading 0.002 m<sup>3</sup>/h

Length 250 mm

Diam. 5 "

PCD 210 mm

## DIMENSIONS

H 299 mm

Install. length 250

PCD 210 mm

**Last modified date: 08/03/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>