# DAB Deep well pump stainless steel 304 1" female thread 5,1A 230VAC with 15m cable and control box booster type Micra 75M oil cooling (7030893)







## **TECHNICAL SPECIFICATIONS**

Material stainless steel 304 Pump body stainless steel 304 Material impeller 1 noryl GFN2 female thread Connection oil cooling Type Voltage 230VAC Max. temperature 35 °C Outer ø 74 mm Minimum medium temperature 0 °C (continuous)  $2.7 \, \text{m}^3/\text{h}$ Max flow rate 1 " Press **BEP Capacity** 1.8 IP value IP68 Micra 75M Type **Output Power** 0,75 HP

with 15m cable and control box booster

Model




Size	1"
Weight	10.2 kg
Power	0.55 kW
Impellers	23
MWC	68
Ampere	5,1 A
BEP Head	42
PORIh	52.9
PORhh	30.3
PORIq	1.3
PORhq	2.2

# **DIMENSIONS**

ØDi-1	1 "
H-1	1145 mm
Db	74 mm







### **PRODUCT INFORMATION**

Includes assembled 15m cable and control box booster.

Pumped liquid: clean, free of solids and abrasives, non-viscous, non-aggressive, and chemically neutral, with properties similar to water.

Maximum permitted amount of sand: 40 g/m3.

Installation: in 3" wells or larger, tanks and cisterns, vertical position. In case of horizontal installation, ensure a minimum load on the thrust assembly.

#### Last modified date: 06/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

