

NaanDan Drip irrigation hose
PE 20 mm x 1,2 mm 47mil 4bar
130micron 1,6ltr/h 30cm black
300m type Amnon PC CNL
(7020702)



NaanDan
by Rivulis

TECHNICAL SPECIFICATIONS

Colour	black
Type	Amnon PC CNL
Material	PE
Filtration	130 micron
Filtration	120 mesh
Flow	1,6 ltr/h
Opening pressure	1 bar
Pressure	4 bar
Rec. press.	1 - 4 bar
Size	20 mm
Length	300 m
Inner ø	17,6 mm
Max. Length	240 m
Dripper spacing	30 cm
Wall thickness	47 mil
Wall thickness	1,2 mm

PRODUCT INFORMATION

The Amnon CNL (Compensated Non-Leakage) flat dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.

Opening Pressure: 1.0 bar.

Closing Pressure: 0.2 bar.

Pressure Regulating Range: 1.0 - 4.0 bar.

Recommended filtration: 130 micron.

Maximum Lateral Length at 0% slope.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal for pulse irrigation in crops growing in bags with soilless media such as strawberries.

Last modified date: 05/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>