


Hunter Irrigation controller plastic 24VAC white/blue type HCC-800 PL 8 stations (7032866)



Hunter®

TECHNICAL SPECIFICATIONS

Colour	white/blue
--------	------------

Type	HCC-800
------	---------

Voltage	24VAC
---------	-------

Number of Stations	8
--------------------	---

IP value	IP44
----------	------

Material	plastic
----------	---------

Type	PL
------	----

Height	305 mm
--------	--------

PRODUCT INFORMATION

The next-generation HCC controller brings the powerful Wi-Fi-based irrigation management capabilities of the industry-leading Hydrowise™ platform to high-end residential, commercial, and public-sector projects. The HCC provides a range of convenient features to monitor larger projects — all with the simple click of a button. The HCC combines robust features of the popular ICC2 controller with automatic, weather-based daily adjustments of Hydrowise programming to create a smart and economical solution for commercial landscape management. HCC can control up to 54 stations* and effectively operate any two stations simultaneously. The controller's convenient modular design allows for rapid expandability with the same 4-, 8-, and 22-station output modules as the ICC2. Engineered with a prewired SmartPort®, HCC is also compatible with Hunter's ROAM and ROAM XL remotes, allowing for fast and reliable manual operation in the field from long-range distances without the need for a smartphone. With a built-in milliamp sensor, troubleshooting faulty wires is a breeze. Easily install an HC Flow Meter to accurately monitor flow, prevent wasted water, and avoid damaged landscapes.

- Number of stations: Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestal)*
- With two-wire EZDS: up to 54 (all enclosure options)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- Any 2 programs or stations can operate simultaneously, providing more efficient watering
- 2 sensor inputs available for use with any Klik sensors and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrawise software
- 31/4" full-color touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

Last modified date: 27/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>