NaanDan Drip irrigation hose PE 20 mm x 1,2 mm 47mil 4bar 130micron 1,1ltr/h 30cm black 300m type Amnon PC CNL (7020697)

NaanDan
by Rivulis

bosta
bringing water to life

TECHNICAL SPECIFICATIONS

Colour	black
Type	Amnon PC CNL
Material	PE
Filtration	130 micron
Filtration	120 mesh
Opening pressure	1 bar
Pressure	4 bar
Rec. press.	1 - 4 bar
Flow	1,1 ltr/h
Size	20 mm
Length	300 m
Inner ø	17,6 mm
Max. Length	300 m
Dripper spacing	30 cm
Wall thickness	47 mil
Wall thickness	1,2 mm

PRODUCT INFORMATION

The Amnon CNL (Compensated Non-Leakage) flat dripper prevents the system from draining which reduces the filling time of the system and allows all plants to receive the same amount of water.
Opening Pressure: 1.0 bar.
Closing Pressure: 0.2 bar.
Pressure Regulating Range: 1.0 - 4.0 bar.
Recommended filtration: 130 micron.
Maximum Lateral Length at 0% slope.
Coefficient of manufacturing Variation (CV): 3%.
Application: ideal for pulse irrigation in crops growing in bags with soilless media such as strawberries.

Last modified date: 25/05/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

bosta
bringing water to life