PSH Pool pump polypropylene 1 1/2" female thread 1,9A 400VAC black type Mini 100T (7032219)



≆ P S H





TECHNICAL SPECIFICATIONS


Shaft stainless steel 416 Pump body PP/GF30 Material impeller 1 noryl Material cover polycarbonate Material seal carbon/ceramic Connection female thread Length 487 mm Max. temperature 40 °C Width 194 mm Height 270 mm Frequency 50 Hz IP value IP55 Motor RPM 2900	Colour	black
Material impeller 1norylMaterial coverpolycarbonateMaterial sealcarbon/ceramicConnectionfemale threadLength487 mmMax. temperature40 °CWidth194 mmHeight270 mmFrequency50 HzIP valueIP55	Shaft	stainless steel 416
Material coverpolycarbonateMaterial sealcarbon/ceramicConnectionfemale threadLength487 mmMax. temperature40 °CWidth194 mmHeight270 mmFrequency50 HzIP valueIP55	Pump body	PP/GF30
Material seal carbon/ceramic Connection female thread Length 487 mm Max. temperature 40 °C Width 194 mm Height 270 mm Frequency 50 Hz IP value IP55	Material impeller 1	noryl
Connectionfemale threadLength487 mmMax. temperature40 °CWidth194 mmHeight270 mmFrequency50 HzIP valueIP55	Material cover	polycarbonate
Length 487 mm Max. temperature 40 °C Width 194 mm Height 270 mm Frequency 50 Hz IP value IP55	Material seal	carbon/ceramic
Max. temperature40 °CWidth194 mmHeight270 mmFrequency50 HzIP valueIP55	Connection	female thread
Width 194 mm Height 270 mm Frequency 50 Hz IP value IP55	Length	487 mm
Height 270 mm Frequency 50 Hz IP value IP55	Max. temperature	40 °C
Frequency 50 Hz IP value IP55	Width	194 mm
IP value IP55	Height	270 mm
	Frequency	50 Hz
Motor RPM 2900	IP value	IP55
	Motor RPM	2900
Type Mini 100T	Туре	Mini 100T
Capacity 18,4 m³/h	Capacity	18,4 m³/h
Output Power 1 HP	Output Power	1 HP



Size	1 1/2"
Voltage	400VAC
Weight	12.2 kg
Power	0.75 kW
MWC	16
Ampere	1,9 A







PRODUCT INFORMATION

Designed for small and medium size residential pools. The great self-priming capacity makes it the ideal pump for filtration and pool cleaners.

Features:

- Connection: female thread
- Self-priming up to 4mwh
- Suitable for operation with salt chlorinators and sea water up to 3,5% (35gr/l)
- High efficiency three phase motor class IE3 according to standard IEC 60034-30-1
- Thermal protection incorporated in single-phase version
- Supplied with 1,5m cable with Schuko plug in single-phase version
- Insulation Class: F
- Protection: IP55



- Motor: 50Hz/2900 rpm with option of 60Hz
- Max water temperature: 40°C

Last modified date: 07/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

