Hunter Pop-up sprinkler plastic 1" female thread 50°-360° black type I-25-04-SS-HS (7026276)



Hunter®

bosta
bringing water to life

TECHNICAL SPECIFICATIONS

Colour	black
Material	plastic
Capacity	0,82 - 7,24 m^3/h
Capacity	13,6 - 120,2 l/min
Connection	female thread
Sector adj. range	50°-360°
Angle	25 °
Max diameter	43.2 m
Radius	11,9 - 21,6 m
Rec. press.	2,5 - 7 bar
Type	I-25-04-SS-HS
Size	1"
WebshopURL	https://www.bosta.com/en-gb/hunter-pop-up-sprinkler-plastic-1-female-thread-50-360-black-type-i-25-04-ss-hs-7026276
Riser height	10 cm

Type I-40															
Nr. 41			Nr. 42			Nr. 43			Nr. 44			Nr. 45			
Bar	Q	R	Bar	Q	R	Bar	Q	R	Bar	Q	R	Bar	Q	R	
3,5	2,32	13,4	3,5	2,50	14,0	3,5	3,23	15,5	4,0	4,54	17,7	4,0	5,00	18,3	
4,0	2,61	13,4	4,0	2,80	14,3	4,0	3,52	15,8	5,0	4,95	17,7	5,0	5,52	18,9	
5,0	2,86	13,7	5,0	3,07	14,9	5,0	3,70	15,8	5,5	5,41	18,3	5,5	5,88	19,5	
5,5	3,07	14,0	5,5	3,27	15,2	5,5	4,11	16,2	6,0	5,66	18,3	6,0	6,25	19,8	

PRODUCT INFORMATION

The Hunter I-25 Strong as iron. That's the I-25 sprinkler. As it has an irrigation radius of 12 to 21 metres, this rotor can be used in zones of different sizes. Playing fields, lawns, flowerbeds: no project is too much. Its compact design can be supplied with an optional stainless steel riser. The I-25 is a reliable, strong and sustainable choice. Let the Hunter I-25 do the hard work for you, day in, day out. Now there's no need for you to do it.

Last modified date: 31/10/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com