Heat exchanger stainless steel 316 1" x 2" female thread MF 260 (0891972)






TECHNICAL SPECIFICATIONS


Material	stainless steel 316
Pressure secondary system	5 bar
Connection	female thread
Pressure primary system	10 bar
Model	MF 260
Capacity kW/h at Δ t=60°C	75 kWh
Flow primary system	35 ltr/min
Flow secondary system	300 ltr/min
Size	1" x 2"
Size secondary system	2 "
Size primary system	1 "

DIMENSIONS

Α	600 mm
В	129 mm
С	430 mm







PRODUCT INFORMATION

Easy to install heat exchanger with tubes of European quality. The Maxi-Flo heat exchanger can only be positioned vertically. The Maxi-Flo heat exchanger can be used to heat your pool by using, for example, the heating of your home. A heat exchanger can quickly heat up the water. In 24 to 48 hours you can reach a water temperature of 28°C. The heat exchanger is therefore an excellent solution if your pool is not used frequently (e.g. weekends only). The Maxi-Flo heat exchangers are also compatible with low temperature circuits of existing geothermal systems or heat pumps. Suitable for chlorine based pools.

Last modified date: 05/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

