

**NaanDan Button dripper**  
**plastic 4/7 mm push-in x**  
**barbed 1,3ltr/h grey/green**  
**type Click Tif, PC (7026014)**



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

|                  |                  |
|------------------|------------------|
| Type             | Click Tif, PC    |
| Material         | plastic          |
| Connection       | push-in x barbed |
| Opening pressure | 0,8 - 0,3 bar    |
| Rec. press.      | 1 - 4 bar        |
| Colour           | grey/green       |
| Flow             | 1,3 ltr/h        |
| Size             | 4/7 mm           |

## PRODUCT INFORMATION

Click Tif PC (Pressure Compensated) on-line button dripper. Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar. Minimum pressure at lateral end: 0.5 bar; Lateral Length exceeding 800m is not recommended. Recommended filtration: 130 micron. For fitting into PE40 pipe, punch 3mm hole. Coefficient of manufacturing Variation (CV): 3%. Application: ideal dripper for crops in uneven terrains where pressure differences are too big and using the CNL type is not possible due to its opening/closing pressure range. The PC type will open at lower pressure and keep open at higher pressures.

**Last modified date: 26/05/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road

Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>