

**NaanDan Button dripper**  
**plastic push-in x taper F 12ltr/h**  
**red/green type Click Tif, PC**  
**(7026018)**



**NaanDan**  
by Rivulis

# TECHNICAL SPECIFICATIONS

Type	Click Tif, PC
Material	plastic
Connection	push-in x taper F
Opening pressure	0,8 - 0,3 bar
Rec. press.	1 - 4 bar
Colour	red/green
Flow	12 ltr/h

## PRODUCT INFORMATION

Click Tif PC (Pressure Compensated) on-line button dripper.

Pressure Regulating Range: 0.5 - 4.0 bar; Minimum Working Pressure: 1.0 bar.

Minimum pressure at lateral end: 0.5 bar; Lateral Length exceeding 800m is not recommended.

Recommended filtration: 130 micron.

For fitting into PE40 pipe, punch 3mm hole.

Coefficient of manufacturing Variation (CV): 3%.

Application: ideal dripper for crops in uneven terrains where pressure differences are too big and using the CNL type is not possible due to its opening/closing pressure range. The PC type will open at lower pressure and keep open at higher pressures.

**Last modified date: 10/03/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road

Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>