

**Profec Gate valve ductile iron
(GGG40) epoxy coating DN250
DIN flange 16bar DN250 blue
PN10 type 301 (0400707)**




TECHNICAL SPECIFICATIONS

Colour	blue
Type	301
Material	ductile iron (GGG40)
Surface treatment	epoxy coating
Operation	handwheel
Colour lever	blue
Handle material	cast iron
Material valve	cast iron EPDM coated
Material spindle	stainless steel
Material housing	ductile iron (GGG40)
Material seal	NBR
Connection	DIN flange
Min. temp.	0 °C
Max. temperature	80 °C
RAL number	RAL5017
Flange according to DIN	DIN 2501/PN10
Pressure	16 bar

Size	DN250
Length	250 mm
Flange	PN10
Outer ø	405 mm
PCD	350/355 mm
Holes	12

DIMENSIONS

Construction length	din 3352/2c/f4
L	250 mm
L	230 mm
PCD	350/355 mm
Ct-1	538 mm
R	370 mm



Last modified date: 02/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>