Flotide Sand filter polyester gelcoated 63 mm / 2" metric/imperial glue socket 2,5bar black type SMG750 (7011876)



FLOTIDE


bosta
bringing water to life

TECHNICAL SPECIFICATIONS

Colour	black
Material	polyester gelcoated
Connection	metric/imperial glue socket
Pressure	2,5 bar
Max. temp.	43 °C
Type	SMG750
Size	63 mm / 2"
WebshopURL	https://www.bosta.com/en-gb/flotide-sand-filter-polyester-gelcoated-63-mm-2-metric-imperial-glue-socket-2-5bar-green-type-smg750-7011876
Diameter	770 mm
Weight	38 kg
Sand	250 kg
Filter area	0.44 m^2
Max flow rate	22.1 m^3/h
Max. pool vol.	110.5 m^3

DIMENSIONS

A	1015 mm
B	30 " inch
B	770 mm
C	603 mm
D	517 mm



PRODUCT INFORMATION

This Gelcoat filter tank has been well-received by the industry due to the durable, trustworthy performance and smooth gelcoat fibreglass finish. With UV-resistant material used, it is able to operate under prolonged sunlight for years of reliability. "SMG" Series side mount filters are equipped with a six-position, side mount multiport valve and ABS laterals. Switch off the pump before each lever action.

- Non corrosive gel coat fibreglass tank
- Smooth finish
- ABS internal pipe work construction
- Transparent lid provides clear view of filter media
- Air release valve
- 6-way multiport sidemount valve
- Warranty period: 2 years

Last modified date: 06/11/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com