

**Profec Submersible pump  
stainless steel 1" x 1 1/4" 8bar  
5,8A 230VAC stainless steel  
with float switch (7036678)**



# TECHNICAL SPECIFICATIONS

Colour	stainless steel
Material	stainless steel
Output Power	0,9 HP
Pump body	stainless steel 304
Material impeller 1	noryl
Voltage	230VAC
Power	0.7 kW
Temperature range	5°C - 35°C
MWC	50
Ampere	5,8 A
Max flow rate	5 m <sup>3</sup> /h
Size	1" x 1 1/4"

## DIMENSIONS

L	800 mm
---	--------

# PRODUCT INFORMATION

Submersible pump with IP68 degree of protection and B insulation class. It comes with a 15m mains cable (H07RN-F 1~230V with plug) and runs at a speed of 2900 rpm. The pump has 1-phase built-in thermal protection and integrated starting capacitor. It can operate at a maximum pressure of 8 bar, immersion depth of 15m, maximum water column above the pump of 22m, maximum delivery head of 50m, and a maximum delivery rate of 5.0 m<sup>3</sup>/h.

**Last modified date: 07/10/2025**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>