

**Profec Water meter dry cast  
iron DN100 DIN flange 10bar  
0,01A 60m<sup>3</sup>/h 24V blue  
LXLC/FX type Woltman  
horizontal with pulse (7019376)**



# TECHNICAL SPECIFICATIONS

Colour	blue
Type	Woltman
Material	cast iron
Model	LXLC/FX
Material flange	cast iron
Material seal	rubber reinforced with nylon
Connection	DIN flange
Pulse	100 ltr
Type	horizontal with pulse
Voltage	24V
Pressure	10 bar
Max. temp.	40 °C
Capacity	100 m <sup>3</sup> /h
Capacity Qmax	120 m <sup>3</sup> /h
Capacity Qn	60 m <sup>3</sup> /h
Size	DN100
Q1 ISO 4064 (2005)	1.25 m <sup>3</sup> /h

Q3 ISO 4064 (2005)	100 m <sup>3</sup> /h
--------------------	-----------------------

Q4 ISO 4064 (2005)	125 m <sup>3</sup> /h
--------------------	-----------------------

Min. reading	0.002 m <sup>3</sup> /h
--------------	-------------------------

Max. reading	999.999 m <sup>3</sup> /h
--------------	---------------------------

Length	250 mm
--------	--------

Diam.	4 "
-------	-----

PCD	180 mm
-----	--------

## DIMENSIONS

H	289 mm
---	--------

Install. length	250
-----------------	-----

PCD	180 mm
-----	--------

## PRODUCT INFORMATION

Output signal: Parallel reed contact (3 wire)

**Last modified date: 09/03/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds

Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>