

# Solenoid valve brass 3/4" female thread 14bar 230VAC type HK (0404100)



# TECHNICAL SPECIFICATIONS

|                             |                       |
|-----------------------------|-----------------------|
| Type                        | HK                    |
| Material                    | brass                 |
| Operation                   | direct servo-operated |
| Indirect effect             | yes                   |
| Material housing            | brass                 |
| Material seal               | NBR                   |
| Connection                  | female thread         |
| Right-angled model          | no                    |
| Deactivated when open       | No                    |
| Voltage                     | 230VAC                |
| Temperature range           | -10°C - 140°C         |
| Power                       | 14 W                  |
| Minimum pressure difference | 0.1 bar               |
| Maximum ambient temperature | 35 °C                 |
| Direct current (DC)         | no                    |
| Capacity                    | 40 l/min              |
| Size                        | 3/4"                  |

Pressure

14 bar

## PRODUCT INFORMATION

This valve will be delivered with an 8 Watt 230V/50Hz coil up to 3/4".  
The 1" version will be delivered with a 14 Watt coil.  
No pressure difference is needed.

**Last modified date: 23/05/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>