

**Profec Gate valve cast iron GG
25 varnished DN65 DIN flange
10bar DN65 black PN10/16
type 200 (0400762)**



TECHNICAL SPECIFICATIONS

Colour	black
Type	200
Material	cast iron GG 25
Surface treatment	varnished
Operation	handwheel
Colour lever	black
Handle material	Cast iron
Material valve	Cast iron
Material spindle	stainless steel
Seat material	brass
Material housing	cast iron GG 25
Material seal	brass
Connection	DIN flange
Max. temperature	100 °C
Flange according to DIN	DIN 2501/PN10
Pressure	10 bar
Size	DN65

Length	170 mm
--------	--------

Flange	PN10/16
--------	---------

Outer ø	185 mm
---------	--------

PCD	145 mm
-----	--------

Holes	4
-------	---

DIMENSIONS

Construction length	din 3352/2c/f4
---------------------	----------------


Ct-1	258 mm
------	--------

L	170 mm
---	--------

L	170 mm
---	--------

PCD	145 mm
-----	--------

R	160 mm
---	--------



Last modified date: 21/08/2026

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds

Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
<http://www.bosta.com>