## Rain Bird Drip irrigation hose PE 16 mm x 1,2 mm 4,1bar 125micron 2,3ltr/h 50cm brown 100m type PC inline XF-D (7021531)



RAIN



## **TECHNICAL SPECIFICATIONS**

Colour	brown
Туре	PC inline XF-D
Material	PE
Filtration	125 micron
Inner ø	13,6 mm
Opening pressure	0,58 bar
Maximum ambient temperature 51,7 °C	
Pressure	4,1 bar
Max. temp.	38 ℃
Rec. press.	0,58 - 4,1 bar
Wall thickness	1,2 mm
Flow	2,3 ltr/h
Size	16 mm
Length	100 m
Max. Length	169 m
Dripper spacing	50 cm



## PRODUCT INFORMATION

The Rain Bird Drip irrigation hose, type PC inline XF-D is ideal for drip irrigation on ground cover, dense plantings, hedge rows, trees and in many other applications.

The brown XF-D drip hose can be fitted with the XF insert and lock type fittings.

The XF-D drip hose pressure compensated range goes from 1.0 up to 3.8bar.

The XF-D special material gives it additional flexibility in order to avoid kinks in the coils before and during installation.

The benefit of this is to save time and material by allowing tighter turns with less fittings and stakes.

The inline drippers have a protected labyrinth which allow it to control the flow more precisely when compared to a round dripper.

## Last modified date: 16/10/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

