

**Profec Foot valve cast iron GG  
25 DN125 DIN flange 16bar  
DN125 stainless steel 304 blue  
PN10/16 (0411505)**



# TECHNICAL SPECIFICATIONS

|                         |                     |
|-------------------------|---------------------|
| Colour                  | blue                |
| Material                | cast iron GG 25     |
| Material filter element | stainless steel 304 |
| Material (spring)       | stainless steel 304 |
| Material housing        | cast iron GG 40     |
| Material seal           | NBR                 |
| Connection              | DIN flange          |
| Temperature range       | -20°C - 85°C        |
| Pressure                | 16 bar              |
| Holes                   | 8                   |
| Size                    | DN125               |
| Length                  | 200 mm              |
| DN                      | 125                 |
| Flange                  | PN10/16             |
| Outer ø                 | 250 mm              |
| PCD                     | 210 mm              |

# DIMENSIONS

|   |        |
|---|--------|
| L | 200 mm |
|---|--------|

|     |        |
|-----|--------|
| PCD | 210 mm |
|-----|--------|

**Last modified date: 07/03/2026**

Bosta UK Ltd.  
Reflection House  
Olding Road  
Bury St. Edmunds  
Suffolk  
IP33 3TA  
T +44 (0) 1284 716580  
E [enquiries@bosta.co.uk](mailto:enquiries@bosta.co.uk)  
<http://www.bosta.com>