# Grundfos Multi-stage centrifugal pump stainless steel 1 1/4" 2,5A 400VAC type CRI 5-7 A CA I V HQQV (7039733)







## **TECHNICAL SPECIFICATIONS**

Material stainless steel

Shaft stainless steel 316

Pump body stainless steel 316

Material impeller 1 stainless steel 304

Voltage 400VAC

Temperature range -20°C - 90°C

Maximum ambient temperature 40 °C

Minimum ambient temperature 0 °C

Type CRI 5-7 A CA I V HQQV

Output Power 1.5 HP

Size 1 1/4"

Power 1.1 kW

Impellers 7

MWC 40

Ampere 2,5 A

Max flow rate 8.5 m<sup>3</sup>/h


Suction 1 1/4 "




Efficiency	82,7 %
Motor RPM	2770

# **DIMENSIONS**

L	160 mm
H-1	649 mm
W-1	210 mm
ØDi-1	35 mm
ØDi-2	35 mm
Cb-1	50 mm
Cb-2	50 mm







### **PRODUCT INFORMATION**

Grundfos CRI pumps are vertical, non-self-priming, multistage, in-line, centrifugal pumps for installation in pipe systems and mounting on a foundation, suitable for industrial applications. This design provides a more compact pump design and pipework. CR pumps are designed for a variety of applications ranging from the pumping of potable water to the pumping of chemicals. The pumps are therefore suitable for a wide range of pumping systems where the performance and material of the pump meet specific demands.

#### Last modified date: 20/11/2025

Bosta UK Ltd.
Reflection House
Olding Road
Bury St. Edmunds
Suffolk
IP33 3TA
T +44 (0) 1284 716580
E enquiries@bosta.co.uk
http://www.bosta.com

