

IDIT Druppelbevloeiingsslang
PE 16 mm x 1,15 mm 46mil
4bar 130micron 2,3ltr/h 30cm
zwart 50m type Non PC
(7006235)



TECHNISCHE SPECIFICATIES

Kleur zwart

Type Non PC

Materiaal PE

Filtrage 130 micron

Filtrage 120 mesh

Werkdruk 4 bar

Aanb. druk 2 bar

Wand 46 mil

Wand 1,15 mm

Afgifte 2,3 ltr/h

Maat 16 mm

Lengte 50 m

Binnen ø 13,7 mm

Max. lengte per streng 59 m

Dripperafstand 30 cm

IDIT					
Bar	Q = LRI - IDIT 16-1.4 ltr	Q = LRI - IDIT 16-2.3 ltr	Q = LRI - IDIT 16-3.1 ltr	Q = LRI - IDIT 16-4.3 ltr	Q = LRI - IDIT 16-10 ltr
0.5	0.9	1.5	2.0	2.8	6.5
1.0	1.3	2.1	2.8	4.0	9.3
1.5	1.6	2.6	3.6	4.9	11.5
2.0	1.9	3.1	4.1	5.7	13.3



bosta
bringing water to life

PRODUCTINFORMATIE

Inline druppelslang op korte rollen, speciaal voor kleinschalige projecten.

Gegenereerd op datum: 24-05-2026

<http://www.bosta.com>